















| YANMAR Engine & Equipment Model | |  | |  | |  | |  | |  | |
|---|--|--|--|--|--|---|--|--|--|---|--|
| 3TNE84D G1, GH, G1A and KOMATSU 3D84E-1FB 3D84E-2FB 3D84E-3FB Bore: 3.30 in 84.00 mm Stroke: 3.54 in 90.00 mm | | Engine O/H Kit | | Piston Kit | | Main Bearing | | Con Rod Bearing | | Thrust Washers | |
| | | YOK3TNE84D | | Y129002-22090 Std. | | Y129001-02931 Std. | | Y129150-23601 Std. | | Y129150-02931 | |
| | | YOK3TNE84D/25 | | Y129002-22910 0.25 | | Y129150-02871 0.25 | | Y129150-23611 0.25 | | | |
| | | | | See note (1) below | | | | | | | |
| | | Use 3 | | Use 4 | | Use 3 | | Set of 4 | | | |
|  | |  | |  | |  | | | | | |
| 1) Front Seal 2) Rear Seal | | 1) O/H Gasket Set | | 1) Bush, Con Rod 2) Bushing, Cam | | 1) Tappet | | | | | |
| | | 2) Head Gasket 3) Liquid Gasket 4) Rocker Cover Gasket | | 3) Bolt, Con Rod | | | | | | | |
| 1) Y129795-01800 2) Y129795-01780 | | 1) YMG3TNE84 2) Y129002-01331 3) Y977770-1207F 4) Y129150-11310 | | 1) Y129100-23910 x3 2) Y129795-02412 x1 3) Y121550-23200 x6 | | 1) Y129150-14200 x6 | | | | | |
|  | | Valve, Intake | | Valve, Exhaust | | Guide, Valve 1) Intake 2) Exhaust | | 1) Lock, Valve 2) Stem Seal Int 3) Stem, Seal Exh | | Spring, Valve | |
| | | Y129100-11100 x3 | | Y129100-11130 x3 | | 1) Y120130-11860 x3 2) Y129150-11810 x3 | | 1) Y27310-080001 x12 2) Y124460-11340 x3 3) Y121400-11340 x3 | | Y129795-11120 x6 | |
|  | |  | |  | |  | | | | | |
| Thermostat | | Oil Pump | | Water Pump | | Repair Sleeve | | | | | |
| Y129155-49801 | | Y129001-32001 | | 1) Y129001-42004 (2) 2) Y129100-42004 (2) 3) Y129263-42000 (2) | | 84RS | | | | | |

(1) Rings only to be used with Bells Engines Pistons (ALFIN).

(2) Check your application for proper usage.