
















<b>YANMAR</b> <b>Engine &amp; Equipment</b> <b>Model</b> <b>4TNV84</b> DMW, GGE, KLAN, KVA, KWA, LU2  Bore: 3.30 in 84.00 mm										
	<b>Engine O/H Kit</b>		<b>a) Piston Kit</b> <b>b) Ring Set</b>		<b>Main Bearing</b>		<b>Con Rod Bearing</b>		<b>Thrust Washers</b>	
	<b><u>YOK4TNV84</u></b>		<b>a) <u>Y129004-22080</u> Std.</b> <u>Y129004-22900</u> 0.25 <b>Use 4</b>		<u>Y129001-02931</u> Std. <u>Y129150-02871</u> 0.25 <b>Use 5</b>		<u>Y129150-23601</u> Std. <u>Y129150-23611</u> 0.25 <b>Use 4</b>		<u>Y129150-02931</u> <b>Set of 4</b>	
	<b><u>YOK4TNV84/25</u></b>		<b>b) <u>Y129004-22500</u> Std.</b> <u>Y129004-22950</u> 0.25							
										
<b>1) Front Seal</b> <b>2) Rear Seal</b>		<b>1) O/H Gasket Set</b>		<b>1) Bush, Con Rod</b> <b>2) Bushing, Cam</b>		<b>1) Tappet</b>				
		<b>2) Head Gasket</b> <b>3) Liquid Gasket</b> <b>4) Rocker Cover Gasket</b>		<b>3) Bolt, Con Rod</b>						
1) <u>Y129795-01800</u> 2) <u>Y129795-01780</u>		1) <u>YMGS4TNE84</u> 2) <u>Y129408-01330</u> 3) <u>Y977770-1207F</u> 4) <u>Y129601-11310</u>		1) <u>Y129100-23910</u> <b>x4</b> 2) <u>Y129795-02412</u> <b>x1</b> 3) <u>Y121550-23200</u> <b>x8</b>		1) <u>Y129150-14200</u> <b>x8</b>				
		Valve, Intake Valve, Exhaust		Guide, Valve 1) Intake 2) Exhaust		1) Stem Seal Int 2) Stem, Seal Exh		Spring, Valve		
<u>Y129005-11100</u> x4 or <u>Y129004-11130</u> x4		<u>Y129100-11112</u> x4		1) <u>Y120130-11860</u> x4 2) <u>Y129150-11810</u> x4		1) <u>Y124460-11340</u> x4 2) <u>Y121400-11340</u> x4		<u>Y129795-11120</u> x8		
										
<b>Thermostat</b>		<b>Oil Pump</b>		<b>Electric Fuel Pump</b>		<b>Water Pump</b>		<b>Repair Sleeve</b>		
<u>Y129155-49801</u>		<u>Y129001-32001</u> <u>Y129407-32000</u>		<u>Y119225-52102</u>		1) <u>Y129001-42004</u> <b>(1)</b> 2) <u>Y129100-42004</u> <b>(1)</b> 3) <u>Y129263-42000</u> <b>(1)</b>		<u>84RS</u>		

(1) Check your application for proper usage.