


KA INFINITY Sealant & Adhesive

Technical Data Sheet



KA BUILDING PRODUCTS
TECHNICAL SUPPORT
+44(0) 1872 879011

DESCRIPTION

KA INFINITY SEALANT is the ultimate performing fast curing, high strength grab adhesive & sealant. KA INFINITY SEALANT can be used for general purpose construction, modular building applications and vehicular bonding of Stone, Concrete, Wood, Brick, Glass, Mirrors, Stainless Steel, Zinc, Aluminium Gypsum Board & most Plastics.

KA INFINITY SEALANT does not shrink and is resistant to UV radiation, chlorine, mould and general weathering. Adhesion to almost all surfaces internally and externally without primer is excellent and will even bond in the wet to damp surfaces.

- » Free of Solvent, Silicone & Isocyanates
- » Low odour and free of Volatile Organic Compounds
- » Bonds in the wet
- » Paintable



DIRECTIONS FOR USE Surfaces to be sealed must be clean, and free from dust, dirt, frost, grease and other contamination. Cut the cartridge tip and applicator nozzle to the required diameter. Screw nozzle onto cartridge. When using as an adhesive: Apply product in small blobs or a continuous wavy bead along the surface to be bonded, offer up firm into position before skin forms.

When using as a sealant: To achieve a clean finish, apply masking tape to adjacent areas where potential exuded adhesive is not wanted.

Apply sealant with applicator gun ensuring good surface contact is achieved.
Wash hands after use.

STORAGE In a cool dry environment, product can be stored for 12 months from its production date in original unopened container, at temperatures between +2°C and + 25°C.

Limitations

Must not be used to seal aquariums or joints subject to continuous water immersion. It is always the user's responsibility to determine suitability of use. It is not recommended for use in areas subject to abrasion.

HEALTH & SAFETY

Use only in well – ventilated areas and avoid contact with skin and eyes.

In case of contact with eyes, rinse immediately with water and seek medical advice.

Wear suitable protective clothing and gloves.

Keep out of reach of children.

About this information

Whilst every care has been taken to ensure that this product can be used for the purpose for which it is intended. Kenyon Agencies Ltd have no control over the way that the product is used, the workmanship or application of the products. The information given here has been compiled on the basis of available knowledge in accordance with the requirements of the Chemical Hazards Information and Packaging Regulation 1997. This does not imply that the information is complete or accurate in all cases and no guarantee can be given that is complete and accurate. It is the user's responsibility to take adequate measures to satisfy themselves as to the application and suitability of the information and/or recommendations given for their own use. Depending on the nature and condition of the applicable surface, it is recommended that users ascertain suitability of product for own use by carrying out sample tests to surfaces as and when necessary. It is recommended that, in order to comply with the terms and conditions of the twenty five year guarantee, qualified operatives should be employed.