



CVE Shop **Black Combi-Flex** is ideal for ventilation, air conditioning, and air handling systems where a high mechanical strength and temperature is required.

This fully flexible reinforced aluminium polyester and PVC, laminated construction encapsulates a high tensile steel wire helix covered with a tough PVC outer duct and an aluminium inner duct.

Technical Data	
Diameter Range	100mm to 400mm
Temperature Range	-30°C to +120°C
Air Velocity	30 m/s maximum
Working Pressure	Maximum 2500 Pa positive
External Colour	Black
Standard Length	6 Metres

Packaging

Each 6 metre length is individually cartoned. This production and packaging configuration ensures that wastage through scrap is kept to a minimum and dramatically reduces the chance of damage in transit or on site.

Installation

Fully extend ducting, then cut to exact length using a sharp knife and pliers/wire cutters (see length calculations below). To fix insulated flex to spigots we recommend the Combi-Vent Flexi-Clip (one at each end).

Sizes Available / Dimensions									
CVE Product Code	CVBF-100	CVBF-125	CVBF-150	CVBF-200	CVBF-250	CVBF-300	CVBF-315	CVBF-355	CVBF-400
Diameter	100mm	125mm	150mm	200mm	250mm	300mm	315mm	355mm	400mm
Length	6m	6m	6m	6m	6m	6m	6m	6m	6m
Temperature	-30°C to +120°C								

