

DTE

Pressure Washer Range



The Nilfisk DTE range of pressure washers are made in the UK and are designed to cope with continuous use in the most demanding operator environments.

Focused on efficiency we specialise in supplying robust industrial pressure washers. The Nilfisk DTE range includes both mobile and stationary hot and cold water pressure washers.

The Nilfisk DTE machines are easy to operate and maintain. They are built with a robust stainless steel cover & stone enamelled steel chassis for durability and excellent reliability resulting in reduced service time & costs.

Each of the machines can also come in multiple different variants of; pressure, flows, sizes and accessories that will best suit your specific needs.

Ideally suited for:

- Automotive Industry
- Valeters
- Vehicle Hire Companies
- Manufacturing & Warehousing
- Plant Hire
- Rail Industry
- Franchised Dealers
- Independent Garages
- Logistics / Distribution



Cold Water Pressure Washers



**400CS
Static**



**400CM
Mobile**

- Low revving brass pump for increased working life and durability
- Ceramic sleeved pistons for durability and extended working life
- Robust stainless steel cover and stove enamelled steel chassis for durability and excellent reliability resulting in reduced service time and costs.
- All models include industrial gun, lance and 9 metre twin wire hose as standard accessories



Hot Water Pressure Washers



**400HM
Mobile**



**400HS
Static**

- Robust design for excellent reliability and a reduction in service time and costs
- Low revving pump for increased working life and durability
- High Pressure Chemical System improves cleaning performance with the efficient use of chemicals
- All models include industrial gun, lance and 9 metre twin wire hose as standard accessories

COLD WATER TECHNICAL DATA

	400CS 240V	400CS 415V	400CS 415V	400CM 110V	400CM 240V	400CM 415V
Max working pressure (bar/psi)	100/1450	150/2175	200/3000	100/1450	100/1450	150/2175
Max water flow rate (litres/min)	12	15	15	12	12	15
Max water inlet temp (°C)	60	60	60	60	60	60
Motor (HP/kW/v)	3/2.2/240	5.5/4/415	7.5/5.5/415	3/2.2/110	3/2.2/240	7.5/5.5/415
Pump type	Brass with 3 ceramic pistons, stainless steel valves and fibre seals					
Chassis/Cover	Stone enamelled / stainless steel (full stainless steel available)					
Dimensions (mm)	L500 x W750 x H400			L900 x W500 x H875		L930 x W580 x H820
Weight (kg)	60	60	60	50	50	60
ITEM NO.	UK15A0110	UK15A0114	UK15A0111	UK15A0102	UK15A0100	UK15A0103

HOT WATER TECHNICAL DATA

	400HS 240V	400HS 415V	400HS 415V	400HM 110V	400HM 240V	400HM 415V	500HM 415V
Max working pressure (bar/psi)	100/1450	150/2175	200/3000	100/1450	100/1450	150/2200	200/3000
Max water flow rate (litres/min)	12	15	15	12	12	15	15
Max water inlet temp (°C)	50	50	50	80	80	80	80
Motor (HP/kW/v)	3/2.2/240	5.5/4/415	7.5/5.5/415	3/2.2/110	3/2.2/240	5.5/4/415	7.5/5.5/415
Pump type	Brass with 3 ceramic pistons, stainless steel valves and fibre seals						
Chassis/Cover	Stove enamelled / stainless steel (full stainless steel available)			Stove enamelled / stainless steel			
Dimensions (mm)	L600 x W850 x H1750			L1150 x W735 x H720			
Weight (kg)	250	250	250	160	160	160	160
ITEM NO.	UK15A0307	UK15A0311	UK15A0309	UK15A0301	UK15A0317	UK15A0302	UK15A0306

Nilfisk Ltd

Nilfisk House · Bowerbank Way · Gilwilly Industrial Estate · Penrith · Cumbria · CA11 9BQ
 Tel.: 01768 868995 (UK) · 01 2943838 (IE)
 Email: sales.uk@nilfisk.com (UK & IE)
 www.nilfisk.co.uk · www.nilfisk.ie

