

Product Code: CL036

Description: 13A 2 Gang Double Pole Switched Socket Outlet



General Information

Dimensions	140mm (W) x 80mm (H) x 42mm (D)	
Finish	Metal Clad Grey	
Materials	Front Plate & Mounting Box: Electrophoretically Coated Steel	Insert & Rocker Switch: Urea
	Rear Housing: Urea	Terminals: Brass
	Terminal Screws: Steel & Yellow Passivated	Contacts: Silver "on-lay" Copper / Brass
	Internal Busbars: Formed Pressed Brass	Earth Strap: Mild Steel
Maximum Voltage	250V~ 50Hz	
Load Rating	13A	
Plate Fixing Centres	120.6mm	
Terminal Size	5mmø	
Terminal Torque	2.0Nm	
Terminal Capacity	3 x 2.5mm ² or 2 x 4mm ²	
Double Pole	Yes	
Twin Earth Terminals	Yes	
Back Box Depth	40mm Supplied	
Termination Type	Screw	
Earth Terminal Provided	Yes	
Back Box Knockouts	7 x 20mm (3 on top, 2 on bottom, 1 on each side)	
Operational Temperature	-5°C to +40°C	
Warranty	10 Years	
Standards	BS 1363-2: 2016 +A1: 2018	

Additional Information

Ensure that the mains supply is isolated before commencing installation and refer to the circuit diagram with the relevant product.
Bare earth cables must always be covered with appropriate sleeving and wired to the earth terminal.